SAFETY DATA SHEET

VERJET MR

Section 1: Identification of the substance/mixture and of the company/undertaking

Product Identifier

Trade Name: VERJET MR

1.2 Relevant identified uses of the substance or mixture and uses advised against.

Material of Use: Industrial applications: Inkjet ink for drop-on-demand digital printing process.

1.3 Details of the supplier of the safety data sheet

COLORJET INDIA LTD.

Address: B-195, PHASE II NOIDA

U.P. INDIA-201305

Ph.: +91 120 4897992

Email: www.colorjetgroup.com

Section 2: Hazards Identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



Warning

Acute Tox. 4 H302 Harmful if swallowed. Skin Irrit. H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

HMIS Ratings: Health: 1 Fire: 2 Physical Hazard: 1 Pers. Prot.: H

Hazard Scale: 0 = Minimal; 1 = Slight; 2 = Moderate; 3 = Serious; 4 = Severe * = Chronic hazard

Classification according to Directive 67/548/EEC or Directive 1999/45/EC





Harmful Xn: R20/21/22; R62

Xi: R36/37/38, R43

R52/53

R phrases: 22: Harmful if swallowed. R phrases: 36: Irritating to eyes.

R 20/21/22 Harmful by inhalation, in contact with skin and if swallowed.

R 36/37/38 Irritating to eyes, respiratory system and skin.

R 43 May cause sensitization by skin contact.

R 52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R 62 Possible risk of impaired fertility.

S 9 Keep container in a well-ventilated place.

S 25 Avoid contact with eyes.

S 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S 36/37 Wear suitable protective clothing and gloves.

S 60 This material and its container must be disposed of as hazardous waste.

S 61 Avoid release to the environment. Refer to special instructions/safety data sheets.

Information concerning particular hazards for human and environment: Not applicable.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The substance is classified and labelled according to the CLP regulation.

Hazard pictograms

Warning

Signal word: Warning Hazard statements:

H302 Harmful if swallowed.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

Precautionary statements:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable. vPvB: Not applicable.



Section 3: Composition/Information on Ingredients

Chemical characterization: Mixture

VERJET MR CYAN

Ingredients	CAS-No.	EINECS	Percent	Classi	fication
				Regulation (EC) No. 1272/2008 [CLP]	67/548/EEC
Synthetic resin	Trade Secret	Trade Secret	1%-5%	_	_
Acrylated amine synergist	Trade Secret	Trade Secret	1%-5%		
Pigment blue 15	147-14-8	205-685-1	1%-5%	_	_
Hexamethylene diacrylate	13048-33-4	235-921-9	5%-10%	H315, H319 P305 , P351, P338	R36/38 S26
Tetrahydrofurfuryl Acrylate	2399-48-6	219-268-7	10%-20%	H315, H319 P305, P351, P338	R36/38 S26
Isodecyl Acrylate	1330-61-6	215-542-5	10%-20%	H315, H319	R36/38
				P305, P351, P338	S26
Other photo sensitive monomers	Trade Secret	Trade Secret	35%-45%	H317, H413 P280	_
polymerization initiator	Trade Secret	Trade Secret	5%-15%	H317, H413 P280	_
Surfactant	Trade Secret	Trade Secret	0.1%-1%	_	_

VERJET MR LIGHT CYAN

Ingredients	CAS-No.	EINECS	Percent	Classification	
				Regulation (EC) No. 1272/2008 [CLP]	67/548/EEC
Synthetic resin	Trade Secret	Trade Secret	1%-5%	_	_
Acrylated amine synergist	Trade Secret	Trade Secret	1%-5%		
Pigment blue 15	147-14-8	205-685-1	1%-3%	_	_
Hexamethylene diacrylate	13048-33-4	235-921-9	5%-10%	H315, H319 P305, P351, P338	R36/38 S26
Tetrahydrofurfuryl Acrylate	2399-48-6	219-268-7	10%-20%	H315, H319 P305, P351, P338	R36/38 \$26
Isodecyl Acrylate	1330-61-6	215-542-5	10%-20%	H315, H319 P305, P351, P338	R36/38 S26
Other photo sensitive monomers	Trade Secret	Trade Secret	35%-45%	H317, H413 P280	_
polymerization initiator	Trade Secret	Trade Secret	5%-15%	H317, H413 P280	_
Surfactant	Trade Secret	Trade Secret	0.1%-1%	_	_



VERJET MR MAGENTA					
Ingredients	CAS-No.	EINECS	Percent	Class	ification
				Regulation (EC) No. 1272/2008 [CLP]	67/548/EEC
Synthetic resin	Trade Secret	Trade Secret	1%-5%	_	_
Acrylated amine synergist	Trade Secret	Trade Secret	1%-5%		
Magenta pigment	Trade Secret	Trade Secret	1%-5%	_	_
Hexamethylene diacrylate	13048-33-4	235-921-9	5%-10%	H315, H319 P305 , P351, P338	R36/38 S26
Tetrahydrofurfuryl Acrylate	2399-48-6	219-268-7	10%-20%	H315, H319 P305, P351, P338	R36/38 S26
Isodecyl Acrylate	1330-61-6	215-542-5	10%-20%	H315, H319 P305 , P351, P338	R36/38 S26
Other photo sensitive monomers	Trade Secret	Trade Secret	35%-45%	H315, H319 P305, P351, P338	R36/38 S26
polymerization initiator	Trade Secret	Trade Secret	5%-15%	H317, H413	P280
Surfactant	Trade Secret	Trade Secret	0.1%-1%	_	_

VERJET MR LIGHT MAGENTA

Ingredients	CAS-No.	EINECS	Percent	Classi	fication
				Regulation (EC) No. 1272/2008 [CLP]	67/548/EEC
Synthetic resin	Trade Secret	Trade Secret	1%-5%	_	_
Acrylated amine synergist	Trade Secret	Trade Secret	1%-5%		
Magenta pigment	Trade Secret	Trade Secret	1%-3%	_	_
Hexamethylene diacrylate	13048-33-4	235-921-9	5%-10%	H315, H319 P305, P351, P338	R36/38 S26
Tetrahydrofurfuryl Acrylate	2399-48-6	219-268-7	10%-20%	H315, H319 P305, P351, P338	R36/38 S26
Isodecyl Acrylate	1330-61-6	215-542-5	10%-20%	H315, H319 P305, P351, P338	R36/38 S26
Other photo sensitive monomers	Trade Secret	Trade Secret	35%-45%	H315, H319 P305 , P351, P338	R36/38 S26
polymerization initiator	Trade Secret	Trade Secret	5%-15%	H317, H413	P280
Surfactant	Trade Secret	Trade Secret	0.1%-1%	_	_



VERJET MR

Revision Date: 07/01/2019

Ingredients	CAS-No.	EINECS	Percent	Classi	fication
				Regulation (EC) No. 1272/2008 [CLP]	67/548/EEC
Synthetic resin	Trade Secret	Trade Secret	1%-5%	_	_
Acrylated amine synergist	Trade Secret	Trade Secret	1%-5%		
Magenta pigment	Trade Secret	Trade Secret	1%-3%	_	_
Hexamethylene diacrylate	13048-33-4	235-921-9	5%-10%	H315, H319 P305, P351, P338	R36/38 S26
Tetrahydrofurfuryl Acrylate	2399-48-6	219-268-7	10%-20%	H315, H319 P305, P351, P338	R36/38 S26
Isodecyl Acrylate	1330-61-6	215-542-5	10%-20%	H315, H319 P305 , P351, P338	R36/38 S26
Other photo sensitive monomers	Trade Secret	Trade Secret	35%-45%	H315, H319 P305 , P351, P338	R36/38 S26
polymerization initiator	Trade Secret	Trade Secret	5%-15%	H317, H413	P280
Surfactant	Trade Secret	Trade Secret	0.1%-1%	_	_

VERJET MR YELLOW

Ingredients	CAS-No.	EINECS	Percent Classification		fication
				Regulation (EC) No.	67/548/EEC
				1272/2008 [CLP]	
Synthetic resin	Trade Secret	Trade Secret	1%-5%	_	_
Acrylated amine synergist	Trade Secret	Trade Secret	1%-5%		
Yellow Pigment	68511-62-6	270-944-8	1%-5%	_	_
II	12049 22 4	225 021 0	50° 100°	H315, H319	R36/38
Hexamethylene diacrylate	13048-33-4 235-921	235-921-9	9 5%-10%	P305, P351, P338	S26
77. 1 1 6 6 14 1.	2399-48-6	219-268-7	10%-20%	H315, H319	R36/38
Tetrahydrofurfuryl Acrylate	2399-48-6	219-268-7		P305, P351, P338	S26
Isodecyl Acrylate	1330-61-6	215-542-5	542-5 10%-20%	H315, H319	R36/38
Isodecyi Acrylate	1330-61-6	213-342-3	10%-20%	P305, P351, P338	S26
Other photo sensitive	Trade Secret	Trade Secret	35%-45%	H315, H319	R36/38
monomers	Trade Secret	Trade Secret	ret 35%-45%	P305, P351, P338	S26
polymerization initiator Trade Se	Trade Secret	Trade Secret	5%-15%	H317, H413	
	Trade Secret	e secret Trade secret	3%-13%	P280	
Surfactant	Trade Secret	Trade Secret	0.1%-1%	_	_



VERJET MR

Revision Date: 07/01/2019

VE	DI	CT	NΛ	D	DI	Λ	CL	,
VE	LJ	EI	IVI	п	DI	-A	L.r	۱

Ingredients	CAS-No.	EINECS	Percent Classification		fication
				Regulation (EC) No. 1272/2008 [CLP]	67/548/EEC
Synthetic resin	Trade Secret	Trade Secret	1%-5%	_	_
Acrylated amine synergist	Trade Secret	Trade Secret	1%-5%		
Carbon black	1333-86-4	215-609-9	1%-5%	_	_
Hexamethylene diacrylate	13048-33-4	235-921-9	5%-10%	H315, H319 P305, P351, P338	R36/38 S26
Tetrahydrofurfuryl Acrylate	2399-48-6	219-268-7	10%-20%	H315, H319 P305, P351, P338	R36/38 S26
Isodecyl Acrylate	1330-61-6	215-542-5	10%-20%	H315, H319 P305, P351, P338	R36/38 S26
Other photo sensitive monomers	Trade Secret	Trade Secret	35%-45%	H315, H319 P305, P351, P338	R36/38 S26
polymerization initiator	Trade Secret	Trade Secret	5%-15%	H317, H413	P280
Surfactant	Trade Secret	Trade Secret	0.1%-1%	_	_

VERJET MR WHITE

Ingredients	CAS-No.	EINECS	Percent	Classi	fication
				Regulation (EC) No. 1272/2008 [CLP]	67/548/EEC
Synthetic resin	Trade Secret	Trade Secret	1%-5%	_	_
Acrylated amine synergist	Trade Secret	Trade Secret	1%-5%		
Titanium Dioxide	13463-67-7	236-675-5	5%-15%	_	_
Hexamethylene diacrylate	13048-33-4	235-921-9	5%-10%	H315, H319 P305 , P351, P338	R36/38 S26
Tetrahydrofurfuryl Acrylate	2399-48-6	219-268-7	10%-20%	H315, H319 P305, P351, P338	R36/38 S26
Isodecyl Acrylate	1330-61-6	215-542-5	5%-10%	H315, H319 P305, P351, P338	R36/38 S26
Other photo sensitive monomers	Trade Secret	Trade Secret	15%-25%	H315, H319 P305 , P351, P338	R36/38 S26
polymerization initiator	Trade Secret	Trade Secret	5%-15%	H317, H413 P280	_
Surfactant	Trade Secret	Trade Secret	0.1%-1.0%	_	_



VERJET MR GL

In am diante	CACN	EINECS	Percent	Classification	
Ingredients	CAS-No,	EINECS	(%)	Regulation (EC) No.	67/548/EEC
				1272/2008 [CLP]	
Synthetic resin	Trade Secret	Trade Secret	5-10	_	_
Acrylated amine synergist	Trade Secret	Trade Secret	1-5	_	_
3,3,5-Trimethtyl	86178-38-3	289-200-9	10–15	H315, H319	R36/38
Cyclohexane Acrylate				P305, P351, P338	S26
T-1-1-1-6-6-14-14	2200 49 6	219-268-7	25-40	H315, H319	R36/38
Tetrahydrofurfuryl Acrylate	2399-48-6			P305, P351, P338	S26
Other photo sensitive	T		10-30	H315, H319	R36/38
monomer	Trade Secret	Trade Secret		P305, P351, P338	S26
2-Isopropylthioxanthone	5495-84-1	226-827-9	5-15	H302	R22
Other polymerization	Tour de Consest	Toods Course	1.5	H317, H413	P280
initiator	Trade Secret	Trade Secret	1–5		
Surfactant	Trade Secret	Trade Secret	0.1-2.0	_	_

Section 4: First Aid Measures

4.1 Description of first aid measures

Eye contact: Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician. **Inhalation:** If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

Skin contact: Remove contaminated clothing and shoes immediately. Wash off with soap and plenty of water for at least 15-20 minutes. Consult a physician.

Ingestion: Rinse mouth with water. Never give anything by mouth to an unconscious person. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

Eye contact: Causes severe eye injury which may persist for several days.

Inhalation: Vapors or mist, especially as generated from heating the material or as from exposure in poorly ventilated areas or confined spaces, may irritate nose, throat/respiratory system.

Skin contact: May cause skin irritation, injury, dermatitis, allergy and/or sensitization.

Ingestion: May cause injury of mouth, throat, and stomach.

Over-exposure signs/symptoms

Eye contact: No specific data. Inhalation: No specific data. Skin contact: No specific data.

Ingestion: No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Section 5: Fire Fighting Measures

5.1 Extinguishing media

Suitable extinguishing media



Alcohol-resistant foam, dry chemical, carbon dioxide (CO2)

5.2 Special hazards arising from the substance or mixture

Carbon monoxides, carbon dioxide, oxides of nitrogen, toxic gases/vapors.

5.3 Advice for firefighters

Wear special chemical protective clothing and use breathing apparatus with independent air supply. Approach fire from upwind and avoid hazardous vapors and toxic decomposition products. Decontaminate or discard any clothing that may contain chemical residues.

5.4 Further information

Applying direct water may be dangerous because fire may expand to surroundings. Use water spray to cool unopened containers

5.5 NFPA Ratings: Health: 1 Flammability: 2 Reactivity: 0

Hazard Scale: 0 = Minimal; 1 = Slight; 2 = Moderate; 3 = Serious; 4 = Severe

Section 6: Accidental Release Measure

Absorb spill with sand or earth then place in a chemical waste container.

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13). Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For disposal see section 13.

Section 7: Handling and Storage

7.1 Handling Keep out of reach of children and do not drink.

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist. Keep away from sources of ignition - No smoking. Take measures to prevent the buildup of electrostatic charge. Make sure cartridge is dry before insertion into printer housing.



7.2 Conditions for safe storage, including any incompatibilities

Store in a cool, dry and dark place. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

7.3 Specific end uses

Inkjet printing

Section 8: Exposure Control/Personal Protection

8.1 Control parameters

Components with workplace control parameters

8.2 Exposure controls

Appropriate engineering controls Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Personal protective equipment

Eye/face protection: Face shield and safety glasses. Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection: Handle with gloves and wear appropriate protective impervious clothing. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices.

Wash and dry hands: The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it.

Body Protection: Complete suit protecting against chemicals. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection: Handle with NIOSH approved air purifying respiratory protection equipment in case ventilation is not adequate. Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US).

Hygiene measures: Wash hands after handling. In case contact with clothing, wash before reuse. Do not eat, drink or smoke in handling or storage area.

Environmental controls: Do not release to the environment.



Section 9: Physical and Chemical Properties

VERJET MR CYAN

Color	Cyan Liquid
Odor	Characteristic Odor
Boiling point/boiling range of ink	No Data Available
Melting Point/Melting Range	No Data Available
Flash Point of Ink	>90 Degree C
Auto Ignition Temperature	No Data Available
Flammability (Solid, Gas)	Not Applicable
Explosive Properties	No Data Available
Vapour Pressure	No Data Available
Specific Gravity	Aprox 1.0
Solubility	No Data Available
Water Solubility	Insoluble
Viscosity	5.0 – 10.0 cps
Ph	Not Applicable
Oxidizing Properties	No Data Available
Vapor Density	Not Applicable

VERJET MR LIGHT CYAN

Color	Cyan Liquid
Odor	Characteristic Odor
Boiling point/boiling range of ink	No Data Available
Melting Point/Melting Range	No Data Available
Flash Point of Ink	>90 Degree C
Auto Ignition Temperature	No Data Available
Flammability (Solid, Gas)	Not Applicable
Explosive Properties	No Data Available
Vapour Pressure	No Data Available
Specific Gravity	Aprox 1.0
Solubility	No Data Available
Water Solubility	Insoluble
Viscosity	5.0 – 10.0 cps
Ph	Not Applicable
Oxidizing Properties	No Data Available
Vapor Density	Not Applicable

MAGENTA VERJET MR

Color	Magenta Liquid
Odor	Characteristic Odor
Boiling point/boiling range of ink	No Data Available
Melting Point/Melting Range	No Data Available
Flash Point of Ink	>90 Degree C
Auto Ignition Temperature	No Data Available



Flammability (Solid, Gas)	Not Applicable
Explosive Properties	No Data Available
Vapour Pressure	No Data Available
Specific Gravity	Aprox 1.0
Solubility	No Data Available
Water Solubility	Insoluble
Viscosity	5.0 – 10.0 cps
рН	Not Applicable
Oxidizing Properties	No Data Available
Vapor Density	Not Applicable

VERJET MR LIGHT MAGENTA

Color	Magenta Liquid
Odor	Characteristic Odor
Boiling point/boiling range of ink	No Data Available
Melting Point/Melting Range	No Data Available
Flash Point of Ink	>90 Degree C
Auto Ignition Temperature	No Data Available
Flammability (Solid, Gas)	Not Applicable
Explosive Properties	No Data Available
Vapour Pressure	No Data Available
Specific Gravity	Aprox 1.0
Solubility	No Data Available
Water Solubility	Insoluble
Viscosity	5.0 – 10.0 cps
pH	Not Applicable
Oxidizing Properties	No Data Available
Vapor Density	Not Applicable

VERJET MR YELLOW

Color	Yellow Liquid
Odor	Characteristic Odor
Boiling point/boiling range of ink	No Data Available
Melting Point/Melting Range	No Data Available
Flash Point of Ink	>90 Degree C
Auto Ignition Temperature	No Data Available
Flammability (Solid, Gas)	Not Applicable
Explosive Properties	No Data Available
Vapour Pressure	No Data Available
Specific Gravity	Aprox 1.0
Solubility	No Data Available
Water Solubility	Insoluble
Viscosity	5.0 – 10.0 cps
Ph	Not Applicable
Oxidizing Properties	No Data Available



ERJET MR	Revision	Date: 07/01/2019
Vapor Density	Not Applicable	
VERJET MR BLACK		
Color	Black Liquid	
Odor	Characteristic Odor	
Boiling point/boiling range of ink	No Data Available	
Melting Point/Melting Range	No Data Available	
Flash Point of Ink	>90 Degree C	
Auto Ignition Temperature	No Data Available	
Flammability (Solid, Gas)	Not Applicable	
Explosive Properties	No Data Available	
Vapour Pressure	No Data Available	
Specific Gravity	Aprox 1.0	
Solubility	No Data Available	
Water Solubility	Insoluble	
Viscosity	5.0 – 10.0 cps	
Ph	Not Applicable	
Oxidizing Properties	No Data Available	
Vapor Density	Not Applicable	
	,	
VERJET MR WHITE		
Color	White Liquid	
Odor	Characteristic Odor	

Color	White Liquid
Odor	Characteristic Odor
Boiling point/boiling range of ink	No Data Available
Melting Point/Melting Range	No Data Available
Flash Point of Ink	>90 Degree C
Auto Ignition Temperature	No Data Available
Flammability (Solid, Gas)	Not Applicable
Explosive Properties	No Data Available
Vapour Pressure	No Data Available
Specific Gravity	Approx 1.0
Solubility	No Data Available
Water Solubility	Insoluble
Viscosity	5.0 – 10.0 cps
рН	Not Applicable
Oxidizing Properties	No Data Available
Vapor Density	Not Applicable

VERJET MR GL

Color	Clear Liquid
Odor	Characteristic Odor
Boiling point/boiling range of ink	No Data Available
Melting Point/Melting Range	No Data Available
Flash Point of Ink	>90 Degree C
Auto Ignition Temperature	No Data Available



Flammability (Solid, Gas)	Not Applicable
Explosive Properties	No Data Available
Vapour Pressure	No Data Available
Specific Gravity	Aprox 1.0
Solubility	No Data Available
Water Solubility	Insoluble
Viscosity	4.0 – 8.0 cps
Ph	Not Applicable
Oxidizing Properties	No Data Available
Vapor Density	Not Applicable

The Physical and chemical data given in Section 9 are typical values for this product and are not intended to be product specifications.

Section 10: Stability and Reactivity

- **10.1 Reactivity:** High temperatures and UV light may cause rapid polymerization.
- 10.2 Chemical stability: Unstable. Polymerize under heat and/or light.
- 10.3 Possibility of hazardous reactions: Not expected
- **10.4 Conditions to avoid:** Elevated temperatures/heat, UV light, when not in use.
- **10.5 Incompatible materials:** Avoid contact with acids, amines, free radical initiators, oxidizing agents.
- **10.6 Hazardous decomposition products:** Carbon monoxide, carbon dioxide, oxides of nitrogen, toxic gases/vapors.

Section 11: Toxicological Information

11.1 Information on toxicological effects

Routes of Overexposure: Eye, skin, inhalation, and oral ingestion

Acute Health Hazards: Overexposure of the eye surface to ink may be mildly irritating. Overexposure of ink contact with the skin may cause irritation and, in some people, swelling and redness.

Intentional inhalation to ink vapors may result in respiratory tract irritation. Intentional or accidental

oral ingestion may cause an upset stomach. **Chronic Health Hazards:** No information available

Mugtagenicity: No information available
Carcinogenicity: No information available
Acute Toxicity Data: Hexamethylene diacrylate,

LD50 Oral, mouse:>2000 mg/kg LD50 Dermal, rabbit: >2000 mg /kg Causes moderate skin irritation Causes moderate eye irritation

Isodecyl Acrylate

LD50 Oral, rat:12,000 mg/kg Causes moderate skin irritation



Causes moderate eye irritation

Tetrahydrofurfuryl Acrylate

Causes moderate skin irritation

Causes moderate eye irritation

The information shown in SECION 3, Hazards identification, is based on toxicity profiles of similar materials or on the components present in this material.

Section 12: Ecological Information

12.1 Toxicity

Acquatic toxicity: No further relevant information available.

- 12.2 Persistence and degradability: No further relevant information available.
- **12.3 Bioaccumulative potential:** No further relevant information available.
- **12.4 Mobility in soil:** No further relevant information available.
- 12.5 Results of PBT and vPvB assessment PBT: Not applicable. vPvB: Not applicable.
- 12.6 Other adverse effects: No further relevant information available.

Section 13: Disposal Considerations

13.1 Waste treatment methods

Product

This combustible material may be burned in a chemical incinerator equipped with an afterburner and scrubber. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging

Dispose of as unused product

Section 14: Transport Information

14.1 UN number

ADR/RID: - IMDG: - IATA: -

14.2 UN proper shipping name

ADR/RID: Not dangerous goods IMDG: Not dangerous goods IATA: Not dangerous goods

14.3 Transport hazard class(es)

ADR/RID: — IMDG: — IATA: —

14.4 Packaging group

ADR/RID: - IMDG: - IATA: -

14.5 Environmental hazards

ADR/RID: no



IMDG Marine pollutant: no

IATA: no

14.6 Special precautions for user

No data available

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

REACH Status: In compliance.

Pre-registration status: All components are listed or exempted.

Annex XIV - List of substances subject to authorization Substances of very high concern None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Not applicable.

15.2 Chemical Safety Assessment

No data available

15.3 Other information

US Regulation:

TSCA Section 4(a) Final Test Rules Regulated: Not regulated.

TSCA Section 8(a) Preliminary Assessment Information Rule (PAIR): Not regulated.

TSCA Section 8(a) Inventory Update Rule: All components on TSCA INVENTORY

TSCA Section 8(d) Health and Safety Study Reporting: Not regulated.

TSCA Section 12(b) One-Time Export Notification Regulated: Not regulated.

California Proposition 65: Not regulated.

Section 16: Other Information

The data in this Material Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.

This information is based upon technical information believed to be reliable. It is subject to revision as additional knowledge and experience is gained.